



BLACK PLUS 95 C

With its well-appointed design, the Black Plus 95 C automotive film combines discretion and privacy from prying eyes with technical efficiency in reflecting solar heat.



SOLAR SCREEN® Warranty

10 YEARS



Fire-resistance rating

M1



Storage from -5°C to +40°C

3 YEARS



REACH RoHS compliant

RESPECTED

WIDTHS AVAILABLE:

51 cm

76 cm

101 cm

152 cm

TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

Ultraviolet transmission	1 %
Visible light transmission	6 %
Reflection of external visible light	6 %
Reflection of internal visible light	5 %
Total solar energy rejected	49 %
Total solar energy rejected 2*	41 %
Solar ratio:	
Solar energy reflection	7 %
Solar energy absorption	55 %
Solar energy transmission	38 %
Reduction in Solar Glare	94 %
g-value	-
u-value	-
Shading coefficient	
Installation type: Internal application	
Roll length	30,5 m
PET / PVC composition	PET

Colour: BLACK

Thickness

INSTALLATION ADVICE

Vertical installation and on standard glass surface**

Clear single pane	V
Tinted single pane	×
Reflective tinted single pane	×
Clear double pane	×
Tinted double pane	×
Reflective tinted double pane	×
Gas-filled double pane - Low E	×
STADIP EXT. clear double pane	×
STADIP INT. clear double pane	×

Caution X Not ✓ Yes recommended

*Recommendations provided on the basis of a glazed surface covering up to 2.5m², contact us for definitive details or to obtain a thermal chock analysis report.


CONSTRUCTION

- 1. "Hard" scratch resistant layer, for durability and ease of maintenance during window cleaning

 2. Dyed polyester without optical distortion

 3. Bonding adhesive

- 4. High optical quality polyester, with anti-heat nano-ceramic particles
 5. PS adhesive, glass polymerization within 15 days
 6. Protection release liner, disposable after installation



MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 0805 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

 40μ

Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time. Consult our guarantee