



OMEGA 485 C

With its well-appointed metallised design, the Omega 485 C automotive film combines discretion and privacy from prying eyes with technical efficiency in reflecting solar heat. Designed to act as a security film, it provides protection by holding shattered glass in place in the event of an impact.



SOLAR SCREEN® Warranty
10 YEARS



Fire-resistance rating
M1



Storage from -5°C to +40°C
3 YEARS



REACH RoHS compliant
RESPECTED

WIDTHS AVAILABLE:

↔ **152 cm**

TECHNICAL DATASHEET


Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

Ultraviolet transmission	1 %
Visible light transmission	15 %
Reflection of external visible light	7 %
Reflection of internal visible light	7 %
Total solar energy rejected	58 %
Total solar energy rejected 2*	50 %
Solar ratio :	
Solar energy reflection	11 %
Solar energy absorption	61 %
Solar energy transmission	28 %
Reduction in Solar Glare	85 %
g-value	0.44
u-value	-
Shading coefficient	
Installation type : Internal application	
Roll length	30,5 m
PET / PVC composition	PET
Thickness	120 µ

Colour : BLACK

CONSTRUCTION

- "Hard" scratch resistant layer, for durability and ease of maintenance during window cleaning
- High optical quality polyester, with anti IR metal particles deposit
- Bonding adhesive
- High optical quality polyester
- Bonding adhesive
- High optical quality polyester
- Reinforced PS Adhesive to accompany the elasticity of the film in case of impact, glass polymerization within 30 days
- Protection release liner, disposable after installation



INSTALLATION ADVICE

Vertical installation and on standard glass surface**

Clear single pane	✓
Tinted single pane	✗
Reflective tinted single pane	✗
Clear double pane	✗
Tinted double pane	✗
Reflective tinted double pane	✗
Gas-filled double pane - Low E	✗
STADIP EXT. clear double pane	✗
STADIP INT. clear double pane	✗

✓ Yes ⚠ Caution ✗ Not recommended

*Recommendations provided on the basis of a glazed surface covering up to 2.5m², contact us for definitive details or to obtain a thermal shock analysis report.

MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 0805 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time. Consult our guarantee vouchers and our general conditions of sale.