

SUPER CLEAR 3 C FILMS SAFETY TRANSPARENT



SUPER CLEAR 3 C

Super Clear 3 C films help secure your windows by ensuring that the glass does not shatter, remaining transparent and retaining its overall integrity in the event of an impact, explosion or fire. Comply with European Standard EN 12600.



TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

Ultraviolet transmission	<1 %
Visible light transmission	93 %
Reflection of external visible light	7 %
Reflection of internal visible light	4 %
Total solar energy rejected	16 %
Total solar energy rejected 2*	17 %
Solar ratio :	
Solar energy reflection	9 %
Solar energy absorption	8 %
Solar energy transmission	83 %
Reduction in Solar Glare	- %
g-value	-
u-value	5.7
Shading coefficient	0.9
Installation type : Internal application	
Roll length	30.5 m
PET / PVC composition	PET
Thickness	90 μ
Colour : TRANSPARENT	

CONSTRUCTION

- 1. "Hard" scratch resistant layer, for durability and ease of maintenance during window cleaning
- High optical quality polyester
 Reinforced PS Adhesive to accompany the elasticity of the film in case of impact, glass polymerization within 30 days
 Protection release liner, disposable after installation

MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 0805 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time. Consult our guarantee vouchers and our general conditions of sale.

SOLAR SCREEN® EUROPEAN SALES CENTER 18 Rue du Commerce L-3895 FOETZ TEL : +352 26 00 84 82 WWW.SOLARSCREEN.EU

INSTALLATION ADVICE

Vertical installation and on standard glass surface**

Clear single pane	\checkmark	
Tinted single pane	\checkmark	
Reflective tinted single pane	\checkmark	
Clear double pane	\checkmark	
Tinted double pane	\checkmark	
Reflective tinted double pane	✓	
Gas-filled double pane - Low E	\checkmark	
STADIP EXT. clear double pane	\checkmark	
STADIP INT. clear double pane	✓	

✓ Yes Caution X Not recommended *Recommendations provided on the basis of a glazed surface covering up to 2.5m².

