



WHITE PRINT PVC

The White Print PVC film can be printed on with any type of printing machine or method. It has a bubble free adhesive guaranteeing the white effect of the film.



SOLAR SCREEN® Warranty
3 YEARS



Storage from -5°C to +40°C
3 YEARS



REACH RoHS compliant
RESPECTED

WIDTHS AVAILABLE:

↔ **152 cm**

TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

Ultraviolet transmission	< 30 %
Visible light transmission	91 %
Reflection of external visible light	7 %
Reflection of internal visible light	6 %
Total solar energy rejected	10 %
Total solar energy rejected 2*	11 %
Solar ratio :	
Solar energy reflection	7 %
Solar energy absorption	8 %
Solar energy transmission	85 %
Reduction in Solar Glare	8 %
g-value	0.88
u-value	5.7
Shading coefficient	0.9


Installation type : Internal application +
External application

Roll length	50 m
PET / PVC composition	PVC
Thickness	100 µ

Colour : WHITE

CONSTRUCTION

1. White monomer PVC
2. Removable polyacrylate solvent adhesive
3. Protection release liner, disposable after installation



MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 0805 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time. Consult our guarantee vouchers and our general conditions of sale.

INSTALLATION ADVICE

Vertical installation and on standard glass surface**

Clear single pane	✓
Tinted single pane	✓
Reflective tinted single pane	✓
Clear double pane	✓
Tinted double pane	✓
Reflective tinted double pane	✓
Gas-filled double pane - Low E	✓
STADIP EXT. clear double pane	✓
STADIP INT. clear double pane	✓

✓ Yes ! Caution ✗ Not
recommended

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².